

•

88<u>3</u>"[2240mm]

80<u>7</u>"[2044mm]

## **TECHNICAL SPECIFICATIONS** MODEL: B4T16-150SC 160S, 4 TINE, 1 1/2 YD3, GRAPPLE, BN24360

1 1/2 YD <sup>3</sup> 4 TINE 160 SERIES	GRAPPLE	
Open	106 "	2692.4mm
Capacity	1.50 yd³	1.15 m³
Cylinder Bore	3 "	76mm
Cylinder Max. Pressure	5000 psi	345 bar
Rotator Max. Pressure	2540 psi	175 bar
Flow (Rotate Circuit)	10 gpm	38 Lpm
Grapple Rotation, At 10 gpm	29 rpi	m
Flow (Open/Close Circuit)	50 gpm	189 Lpm
Cycle Time Theoritical (Open/Close Circuit)	1.5 sec/2 sec	
Weight (with rotator)	3640 lb	1651 kg

5 Winstar Road Oro-Medonte, ON L0L 2L0, Canada

52<del>1</del>"[1324mm]

-106<u>7</u>"[2704mm]-

-114<u>1</u>"[2897mm]-

Ē

info@batemanmanufacturing.com batemanmanufacturing.com

705-487-5020



GRYB

2023-10-27

WE RESERVE THE RIGHT TO CHANGE SPECIFICATIONS AND TO IMPROVE OUR PRODUCTS WITHOUT NOTICE OR OBLIGATION ALL SCRAP AND MATERIAL HANDLING GRAPPLES DESIGNED IN ACCORDANCE WITH ASME BTH-1 DESIGN AND STRENGTH REQUIREMENTS

 $102\frac{11}{16}$ "[2608mm]

 $42\frac{7}{8}$ "[1090mm]