



BATEMAN

CLAMSHELL BUCKET

BCS10-15

Bateman Clamshell Buckets provide the best solution for loading, re-handling & digging. Our Hydraulic Clamshell Buckets come in light, medium & heavy-duty models with either open or closed back designs.

Heavy-Duty Bearing Rotators.

360 Degrees of Continuous Rotation.

High-Abrasion Resistant Alloy Steel on Leading Edges.

Bolt-on Edges for Extra Wear Protection.

BCS10

MEDIUM/LIGHT

CAPACITY YD ³	WIDTH IN	ESTIMATED GA WEIGHT LBS	NO. OF CYLINDERS	CYLINDER BORE	MATERIAL DENSITY
1/2	24	TBD	2	3	Medium density
3/4	24	TBD	2	3	Medium density
1	36	TBD	2	3	Medium density
1 1/4	36	TBD	2	3	Medium density

Weight is subject to change. Optional bolt-on edges and side cutters available.

BCS15

MEDIUM/LIGHT

CAPACITY YD ³	WIDTH IN	ESTIMATED GA WEIGHT LBS	NO. OF CYLINDERS	CYLINDER BORE	MATERIAL DENSITY
1	48	TBD	2	3.5	Low density
1 1/4	48	TBD	2	3.5	Low density
1 1/2	48	TBD	2	3.5	Low density
2	48	TBD	2	3.5	Low density
2 1/2	60	TBD	2	3.5	Low density
3	60	TBD	2	3.5	Low density

Weight is subject to change. Optional bolt-on edges and side cutters available.

MEDIUM

CAPACITY YD ³	WIDTH IN	ESTIMATED GA WEIGHT LBS	NO. OF CYLINDERS	CYLINDER BORE	MAX MATERIAL DENSITY LBS/FT ³ (LBS/YRD)
1	48	3,800	2	3.5	55 (1,500)
1 1/2	48	4,050	2	3.5	55 (1,500)
2	48	4,200	2	3.5	55 (1,500)
2 1/2	60	4,400	2	3.5	55 (1,500)
3	60	4,500	2	3.5	55 (1,500)

Weight is subject to change. Bolt-on edges and side cutters included.

HEAVY-HDO/SCALLOPED

CAPACITY YD ³	WIDTH IN	ESTIMATED GA WEIGHT LBS	NO. OF CYLINDERS	CYLINDER BORE	MAX MATERIAL DENSITY LBS/FT ³ (LBS/YRD)
1	48	4,000	2	3.5	130 (3,500)
1 1/2	48	4,200	2	3.5	130 (3,500)
2	48	4,400	2	3.5	130 (3,500)
2 1/2	60	4,600	2	3.5	130 (3,500)
3	60	5,000	2	3.5	130 (3,500)

Weight is subject to change. Bolt-on edges and side cutters included.