



**BATEMAN**

# CLAMSHELL BUCKET

**BCS2**

Bateman Clamshell Buckets provide the best solution for loading, re-handling & digging. Our Hydraulic Clamshell Buckets come in light, medium & heavy-duty models with either open or closed back designs.

**Heavy-Duty Bearing Rotators.**

**360 Degrees of Continuous Rotation.**

**High-Abrasion Resistant Alloy Steel on Leading Edges.**

**Bolt-on Edges for Extra Wear Protection.**

## BCS2

### MEDIUM/LIGHT

CAPACITY YD <sup>3</sup>	WIDTH IN	ESTIMATED GA WEIGHT LBS	NO. OF CYLINDERS	CYLINDER BORE	MATERIAL DENSITY
2	48	TBD	2	4	Low density
2 1/2	48	TBD	2	4	Low density
3	60	TBD	2	4	Low density
3 1/2	60	TBD	2	4	Low density
4	72	TBD	2	5	Low density
4 1/2	72	TBD	2	5	Low density
5	84	TBD	2	5	Low density
5 1/2	84	TBD	2	5	Low density
6	84	TBD	2	5	Low density

Weight is subject to change. Bolt-on edges available in option.

### MEDIUM

CAPACITY YD <sup>3</sup>	WIDTH IN	ESTIMATED GA WEIGHT LBS	NO. OF CYLINDERS	CYLINDER BORE	MAX MATERIAL DENSITY LBS/FT <sup>3</sup> (LBS/YRD)
2	48	5,450	2	4	55 (1,500)
2 1/2	48	5,550	2	4	55 (1,500)
3	60	5,680	2	4	55 (1,500)
3 1/2	60	5,800	2	4	55 (1,500)
4	72	6,000	2	5	55 (1,500)
4 1/2	72	6,300	2	5	55 (1,500)
5	84	7,100	2	5	55 (1,500)
5 1/2	84	7,400	2	5	55 (1,500)
6	84	7,700	2	5	55 (1,500)

Weight is subject to change. Bolt-on edges and side cutters included.

### HEAVY-HDO/SCALLOPED

CAPACITY YD <sup>3</sup>	WIDTH IN	ESTIMATED GA WEIGHT LBS	NO. OF CYLINDERS	CYLINDER BORE	MAX MATERIAL DENSITY LBS/FT <sup>3</sup> (LBS/YRD)
1 1/2	48	5,500	2	4	130 (3,500)
2	48	5,600	2	4	130 (3,500)
2 1/2	48	5,700	2	4	130 (3,500)
3	60	5,800	2	4	130 (3,500)
3 1/2	60	6,200	2	4	130 (3,500)
4	72	6,300	2	5	130 (3,500)
4 1/2	72	6,700	2	5	130 (3,500)
5	84	7,000	2	5	130 (3,500)
5 1/2	84	7,500	2	5	130 (3,500)
6	84	8,000	2	5	130 (3,500)

Weight is subject to change. Bolt-on edges and side cutters included.